

# DRIVER COURANT CONSTANT 1-10V I DALI



## Driver 1-10V

Référence	Tension	Courant	Puissance	IP	Dimensions(mm)	Poids
MW-LCM-25	6-54 V	350 mA	18.9 W	20	150 x 68 x 23	0.16 kg
	6-50 V	500 mA				
	6-42 V	600 mA				
	6-48 V	700 mA	25 W			
	6-28 V	900 mA				
	6-24 V	1050 mA				
MW-LCM-40	2-100 V	350 mA	42 W	20	123 x 82 x 23	0.24 kg
	2-80 V	500 mA				
	2-67 V	600 mA				
	2-57 V	700 mA				
	2-45 V	900 mA				
	2-40 V	1050 mA				
MW-LCM-60	2-90 V	500 mA	60 W	20	123 x 82 x 23	0.24 kg
	2-90 V	600 mA				
	2-86 V	700 mA				
	2-67 V	900 mA				
	2-57 V	1050 mA				
	2-42 V	1400 mA				



## Driver DALI (compatible PushDim)

Référence	Tension	Courant	Puissance	IP	Dimensions(mm)	Poids
MW-LCM-25DA	6-54 V	350 mA	18.9 W	20	150 x 68 x 23	0.16 kg
	6-50 V	500 mA				
	6-42 V	600 mA				
	6-48 V	700 mA	25 W			
	6-28 V	900 mA				
	6-24 V	1050 mA				
MW-LCM-40DA	2-100 V	350 mA	42 W	20	123 x 82 x 23	0.24 kg
	2-80 V	500 mA				
	2-67 V	600 mA				
	2-57 V	700 mA				
	2-45 V	900 mA				
	2-40 V	1050 mA				
MW-LCM-60DA	2-90 V	500 mA	60 W	20	123 x 82 x 23	0.24 kg
	2-90 V	600 mA				
	2-86 V	700 mA				
	2-67 V	900 mA				
	2-57 V	1050 mA				
	2-42 V	1400 mA				